

# 360 TOWERLIGHT HEAD

## 3M TRIPOD

This robust, innovative, 110V floodlight features a high lumen output of 84,000 lm and 360° light distribution, also can be linked to two additional TowerLight's for extra coverage, making it an incredibly efficient solution for site lighting.



### Features

- 84000 lm, ideal for large spaces
- Interlink two additional towerlights
- 300W (3 Head) version available as special order
- 20 lux over 2800 m<sup>2</sup> at height of 3m
- Adjustable for 180° and 360° light distribution
- Tripod adjustable to 3 metres
- 10m rubber power cable & carry bag
- Supplied with inline dimmer and on off switch
- Integrated photocell with on/off switch



### Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
TWL360-600	360 TowerLight 600W Head	84,000 lm		600W	140 lm/w

### Product Information

Guarantee	3 Years
Colour Appearance (CCT)	6500K
IP Rating	IP65
IK Rating	IK08
Voltage	100-240V
Material (Body/Housing)	Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	>80

Colour Finish	Yellow
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Dimmable
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 45°C



# 360 TOWERLIGHT HEAD

## 3M TRIPOD

### Packaging Information

Dimensions (mm)	L: 286 x W: 298 x D: 435 mm
Product Net Weight (kg)	14.5 kg
Barcode	5055807626354
Units/Outer Carton	1

Outer Carton Barcode	5055807626354
Outer Carton Dimensions (mm)	L: 330 x W: 300 x D: 505 mm
Outer Carton Gross Weight (kg)	14.5 kg

